



DEKAL[®] LOAD BANKS

DEKAL LOAD BANKS – DEKAL AGREGATI LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA - EUROPE
Tel.: +386 2 320 325 0
Email: info@ekalloadbanks.com
Web: www.dekalloadbanks.com



DEKAL LOAD BANKS USA LLC
c/o CATALYST CONNECTION
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 - USA

Tel.: +1 800 323 9172
Email: info@ekalloadbanks-us.com
Web: www.dekalloadbanks-us.com



Y – CONNECTION CABLE

SPECIFICALLY DESIGNED RUGGED UNITS USED TO CONNECT SINGLE GPU UNIT WITH TWO PORTABLE LOAD BANKS FOR TESTING AND SERVICING OF 400 Hz AC 115 / 200 V GPUs



TECHNICAL SPECIFICATION

YCN-400

VOLTAGE [V]	1150 / 200 V AC \pm 10 %
FREQUENCY [Hz]	400 Hz \pm 10 %
MAX POWEER / CURRENT	208 kW / <600 A For MAX. 5 MINUTES
DETAILED SPECIFICATIONS	SINGLE GPU INPUT TWO SOCKETS - MASTER & SLAVE PLUG WITH CABLE INCLUDED
TESTING PROCEDURE ACCORDING	ISO 6858, DSF 400, ARP 5015
DEVICE CLASSIFICATION	CE marking, DIN, VDE, IEC
DEGREE OF PROTECTION	IP 21
DIMENSIONS (w.o cables) [L x B x H] / [mm / kg]	330 x 180 x 135 / 2,5 kG
CABLE LENGTH	2 x 3 m
COLOR OPTIONS	YELLOW, RED, BLACK ; others on request
ENVIRONMENT	
OPERATING TEMPERATURE	- 20 to 55 °C
RELATIVE HUMIDITY	0%- 85%(w/o condensation)

Including carrying & shipping case per unit / All specifications are subject to change without further notice