

DEKAL[®] LOAD BANKS

DEKAL LOAD BANKS - DEKAL POWER LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA - EUROPE

Tel.: +386 2 320 325 0
Email: info@dekalloadbanks.com
Web: www.dekalloadbanks.com

DEKAL LOAD BANKS USA LLC
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 - USA

Tel.: +1.800.323.9172
Cell: +1.954.516.4245
Email: info@dekalloadbanks-us.com
Web: www.dekalloadbanks-us.com



REACTIVE 56 kVAr MOBILE LOAD BANK with DIGITAL POWER METER; WiFi & USB CONNECTION CAPABLE

SPECIFICALLY DESIGNED RUGGED UNIT FOR
TESTING & DIAGNOSE OF VARIOUS 400 Hz AC
POWER SOURCES WITH LAGGING POWER FACTOR
AND UNIQUE PDF TEST REPORT




TECHNICAL SPECIFICATION

ALB-I-56DW

FREQUENCY [Hz]	400 Hz AC \pm 5 %			
LOAD [kVAr]	0 - 56 kVAr \pm 5 %			
3 LINE HIGH BRIGHTNESS RED LED DISPLAY CLASS: \pm 0.5% FS+2C	V / A / Hz / kW / kVAr / PF			
WiFi & USB INTERFACE SPECIFICATIONS	WiFi NETWORK OR USB PLUG-IN CONNECTION FOR DATA PRINTOUT/ARCHIVE, INCLUDING FREE DEKAL LICENSED SOFTWARE & USB CABLE			
REACTIVE LOADBANK RATE SWITCH REG. LOAD STEPS \pm 5% ROUGH ADJUSTMENTS - 8 kVAr EACH STEP 8, 16, 24, 32, 40, 48, 56 kVAr	kW	kVA	kVAr	PF
In parallel connection with any DEKAL RESISTIVE LOAD BANK	8	8	0	1
	16	16	0	1
	24	30	8	0.95
	32	40	16	0.90
	40	50	24	0.84
	48	60	32	0.83
	56	70	40	0.82
	64	80	48	0.81
	72	90	56	0.80
TYPE OF CONNECTION	400 Hz 6-Pole compatible with NATO and MIL-C-81790			
400 Hz 6-Pole compatible MIL-C-81790	In accordance with STANAG 3456(7) and MIL-STD-704F			
LOAD BANK TYPE & CONFIGURATION	MOBILE by integrated wheels, STATIC with frame adapter			
RESISTIVE LOAD BANK CONNECTION	New DEKAL patented concept with slide-in option			
FORCED AIR COOLING [m ³ /min - CFM]	Constant 44.10 M³MIN - 1560 CFM			
SIZE, WEIGHT & CLASSIFICATION				
TESTING PROCEDURE IN ACCORDANCE	ISO 6858, IP 21, DSF 400, MIL-SPEC ARP, 5015			
LOAD BANK SIZE [L x W x H] mm / Kg	980 x 450 x 800 / 217.5			
LOAD BANK SIZE [L x W x H] In / Lbs	38.6 x 17.7 x 31.5 / 478			

All specifications are subject to change without further notice



DEKAL LOAD BANKS®

DEKAL LOAD BANKS * DEKAL POWER LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA - EUROPE



DEKAL LOAD BANKS USA LLC
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 - USA



Tel.: +386 2 320 325 0 * Fax: +386 2 320 325 2
Email: info@dekalloadbanks.com
Web: www.dekalloadbanks.com

Tel.: +1.800.323.9172 * Cell: +1.954.516.4245
Email: info@dekalloadbanks-us.com
Web: www.dekalloadbanks-us.com

ADVANTAGES of REACTIVE LOAD BANK

- **Simple operation** suitable for non-trained operators and personnel, no maintenance required
- Suitable for **workshop or airside** operation; silent unit rated at <70 dB(A) at 7m / 23Ft
- **Mobile reactive unit with predetermined and controllable capacity of 56 kVAR**
- **Fully mobile** by integrated wheels and **simple conversion to stationary unit** if required
- **New patented concept with slide-in option** to attach any Dekal resistive 400Hz AC unit
- **No cable inconvenience when reactive & resistive units are combined for testing**
- **Fully adjustable load parameters in seven sequence steps**; each rated at 8 kVAR
- **Digital load banks do not require any further calibration process once delivered**
- **Free DEKAL licensed software application & proper drivers included**
- **All measurements possible to archive & printout, including diagram graphics**
- **In accordance & fully complied with AFI 33-115 volume 2, Certified by: SAFIA6C**
- 400 Hz AC 6-Pole receptacle **in accordance with NATO & MIL-C-81790** specification
- **First advanced digital indication of Voltage [V], Current [A] and Frequency [Hz]**
- Housing made of **non-corrosive parts with component quality control** by the manufacturer
- **High reliability with multiple thermal protection** - extremely resistant to high temperature
- **Extra safety and isolated jack sockets** for connecting external measurement device
- **Short worldwide delivery period** with tracking feature and insurance for all products
- Spare parts availability and **accurate on-time deliveries** by appointed courier
- **2 years full warranty with extension option** for all DEKAL load banks
- **Classification CE** marking, DIN, VDE, IEC, **IP 21 protection rate level**
- CE certification - health, safety, and environmental protection standards
- Customs classification **Harmonized System tariff code HS: 8516808000**



NCAGE CODE: 1267Q



Excellent SME



Highest Creditworthiness



D-U-N-S® REGISTERED™